

Cabot's Natural Decking Oil

AUDW0657

Part A	839-line
---------------	----------

Description
<p>Cabot's Natural Decking Oil is a fast drying penetrating oil that nourishes and protects the timber. Its unique oil based formulation can now be recoated in just 6 hours so that you can get two coats on in a day. Cabot's Natural Decking Oil provides protection to timber from the most damaging environmental factors to extend the life of your exterior decking, garden furniture, fences, gates, and pergolas.</p>



Features
<ul style="list-style-type: none"> • UV protection. • Water repellent. • Deep penetrating oil. • Fast recoat. • Dirt and mould resistant.

Benefits
<ul style="list-style-type: none"> • Blocks out harmful UV rays preventing them from penetrating and damaging the surface while resisting colour fade. • Cabot's Natural Decking Oil forms a water repellent barrier aiding protection against mould and minimises cracking and splitting. • Cabot's Natural Decking Oil penetrates the timber to nourish and protect the timber fibres below the surface. • Recoat after only 6 hours so you can get 2 coats done in a day. • Contains powerful ingredients to resist the growth of wood staining mould while the unique formula provides excellent dirt and stain resistance.

Uses
Exterior new and weathered timber including decks, pergolas, fences, gates and garden furniture.

Precautions And Limitations
<p>Do not apply this product in temperatures below 10°C or above 35°C, or when rain or heavy dew is expected during the drying period. In hot temperatures, do not apply in direct sunlight and coat in the shade.</p>

Performance Guide			
Weather	For exterior use.	Salt	Unaffected by splash or spillage
Heat Resistance	Up to 120C.	Water	Good water repellency
Solvent	Resists mineral turpentine and similar solvents.	Abrasion	Good resistance to foot traffic.
Acid	N/A	Alkali	N/A

Typical Properties																											
Gloss Level	Matt	Colour	Natural + 4 shades to match timber species																								
Components	1	Number Of Coats	2																								
Toxicity	Lead free	V.O.C. Level	< 540g/L																								
Touch Dry	3 hours																										
Clean Up Description	Mineral turpentine. To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.																										
Application Method	  Brush Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">22</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">100</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td style="text-align: center;">22</td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">6 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td style="text-align: center;">10</td> </tr> </table>			Solids By Volume	22				Min	Max	Recommended	Wet Film Per Coat (microns)			100	Dry Film Per Coat (microns)			22	Recoat Time (min)	6 hours			Theoretical Spread Rate (m²/L)			10
Solids By Volume	22																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			100																								
Dry Film Per Coat (microns)			22																								
Recoat Time (min)	6 hours																										
Theoretical Spread Rate (m²/L)			10																								
Typical Properties Notes	SPREADING RATE Approximately 10 square metres per litre depending on the porosity and condition of the timber. DRYING AND RECOAT TIME All timings quoted at 25C and 50% humidity. Cooler or humid conditions may require longer.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> • BARE TIMBER To coat new bare timber immediately, scrub damp timber with Cabot's New Timber Prep, following label instructions. New Timber Prep will draw out tannins and oils quickly from the surface, allowing you to skip the 4-6 weeks weathering process required for new timber. Always follow New Timber Prep with Cabot's Deck Clean following label instructions. PREVIOUSLY PAINTED OR VARNISHED TIMBER Remove back to bare timber using a paint stripper, or sanding. For exterior surfaces clean with Cabot's Deck Clean following label instructions. PREVIOUSLY STAINED OR OILED TIMBER For exterior surfaces clean with Cabot's Deck Clean following label instructions, then allow timber to fully dry. Test if the surface is ready for coating by sprinkling water on the timber. If the water beads on the surface, repeat the application of Cabot's Deck Clean. If the water is absorbed into the timber, it is ready for coating. For a more transparent look, sand timber back to bare before coating. WEATHERED AND GREY TIMBER For best results, sand timber back to a fresh substrate. For exterior surfaces clean with Cabot's Deck Clean following label instructions. <p>NOTE: Fill holes and imperfections with a suitable putty.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> • Stir thoroughly with a broad paddle before and during use. Apply liberally along the length of the board including exposed edges and end grain by brush or pad applicator. Apply two coats allowing 6 hours between coats. MAINTENANCE Re-apply as the timber changes colour or when water repellency diminishes due to weathering. Follow surface preparation instructions.

Health And Safety			
MSDS Number	14182401	Using Safety Precautions	RISK: Flammable. Irritating to skin. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. If painting large areas wear an organic vapour respirator. This paint is flammable, so eliminate any sources of ignition. Do not smoke.
Health Effects	If poisoning occurs, contact a doctor or Poisons Information Centre AUST 131 126, NZ 0800 764 766. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. For further information or a copy of the Product Safety Data Sheet telephone Cabots Customer Service department on AUST 1800 011 006, NZ 0800 222 687. For emergencies phone AUST 1800 033 111, NZ 0800 734 607.	Flammability	This product is flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Keep out of reach of children.
Disposal	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Pack A	839-line	Shipment Name	PAINTS
Size	20L 10L 4 L 1 L	Weight	18.8Kg 9.2Kg 3.7Kg 0.99Kg
Flash Point	48C	UN Number	1263
Dangerous Goods Class	3	Package Group	III
Shipment Name	PAINTS		

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427