

INSTALLATION INSTRUCTIONS It is recommended that this product be installed by a licensed plumber in compliance with AS/NZS 3499. Find a plumber via our PlumbConnect Registry by scanning the QR code. Turn off water supply & remove old hose. Clean all connecting threads. Install new connector. Test for leaks.



This connector is to be used with water only in exposed locations. Do not use inside walls or underground. Do not overtighten nuts. Do not stretch, twist or kink the connector. Do not expose to naked flames, household cleaners or corrosive agents. Clean with water only. Keep away from heat. Do not connect to instant hot water heaters. For further instructions refer to the relevant code requirements. Inspect hose regularly. Replace if showing signs of wear, or within 5 years of installation date.

WARRANTY 5 year product warranty from the date of purchase. This warranty covers any defects in materials or workmanship with the exception of the reasons stated below. The warranty covers the product for normal domestic use only. This warranty does not cover wear & tear to working parts, misuse or abuse. It does not cover discolourations due to exposure to sunlight or cleaning chemicals.

Our products come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure & for compensation for any other loss or damage. You are also entitled to have the goods repaired if the goods fail to be of acceptable quality & the failure does not amount to a major failure.

If you believe you have a claim please go to www.fixatap.com.au/warranty. Please keep your receipt for proof of purchase. Any expenses incurred in making the claim will be the responsibility of the consumer.
FIX-A-TAP® AUST. PTY LTD Ph: (02) 9476 7400, PO Box 200, Wahroonga NSW 2076 Australia.
www.fixatap.com.au.

Made in China



AS/NZS 3499
21270
SAI GLOBAL
TRI101-LF

NOTE DATE OF
INSTALLATION:

BOSTON®

GREAT VALUE SOLUTIONS

\$\$

QTY.2



**RUST
RESISTANT**

FLEXI-TUFF® MIXER TAP HOSE EXT.
250MM (9.8") x 1/2" (F) x 1/2" (M) BSP

- Superior polymer braiding to prevent damage from rust.
- PEX inner tube with 8mm bore for a longer life & improved strength.
- Operating temperature up to 90°C for greater heat resistance.
- Operating pressure up to 1200kPa or 174psi.
- Suitable for hot & cold water.

