

# **TORNADO**

# 24 W (100 W) B22 cap Cool daylight Spiral energy saving bulb

The Helix range is a twist-shape compact fluorescent lamp, with optimal light distribution. It is available in 11W, 15W, 20W and 23W (25W), with lumen equivalence of 60W, 75W, 100W and 125W incandescent light bulb. It is also available in two color temperatures: warm white (2700K) and cool daylight (6500K). It is available in both 220-240V and 120-127V and able to operate under a wide voltage range (Power supply fluctuation). It consumes up to 80% less energy than the incandescent light bulb and lasts for 3 years.

#### Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

#### Product data

General Information		
Cap-Base	B22	
Nominal lifetime	8,000 h	
Switching Cycle	5,000	
Rated Lifetime (Hours)	8,000 h	
Lighting Technology	Compact Fluorescent Integrated	
Light Technical		
Color Code	865 [CCT of 6500K]	
Luminous Flux	1,450 lm	
Color Designation	Cool Daylight	
Luminous Efficacy (rated) (Nom)	63 lm/W	

Chromaticity Coordinate X (Nom)	313
Chromaticity Coordinate Y (Nom)	337
Correlated Color Temperature (Nom)	6500 K
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	23 W
Lamp Current (Nom)	170 mA
Starting Time (Nom)	0.3 s

Datasheet, 2024, March 31 data subject to change

## **TORNADO**

Power Factor (Fraction)	0.6
Voltage (Nom)	220-240 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Shape	Spiral
Approval and Application	
Mercury (Hg) Content (Nom)	2 mg
Energy Consumption kWh/1000 h	23 kWh
Product Data	
Order product name	24 W (100 W) B22 cap Cool daylight Spiral

energy saving bulb

Full product name	24 W (100 W) B22 cap Cool daylight Spiral	
	energy saving bulb	
Full product code	871829113817400	
Local code description	TND24WCDLBC	
Order code	929689858602	
Material Nr. (12NC)	929689858602	
Local order code	TND24WCDLBC	
Numerator - Quantity Per Pack	1	
Net Weight (Piece)	0.077 kg	
EAN/UPC - Product/Case	8718291138174	
Numerator - Packs per outer box	6	
EAN/UPC - Case	8718291138181	

## Dimensional drawing



Product	D (max)	C (max)	F (max)
24 W (100 W) B22 cap Cool daylight Spiral energy saving	61.5 mm	117 mm	50.5 mm
bulb			



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.